



# MECMAR

INDUSTRIAL GRAIN DRIERS

FSN Range



FSN 15 T - Tractor drive, oil fired



Galvanised intake auger tube,  
bottom boot and inspection door



Solid shaft drive system



Galvanised steel cable

# OPTIONS

## DRIVE

Selecting a suitable drive option for a grain drier may significantly reduce operating costs. Mecmar drive options include tractor drive, four motor electric drive and dual drive.



TRACTOR DRIVE



FOUR MOTOR  
ELECTRIC DRIVE



DUAL DRIVE

## AUTOMATION

A well specified automated system may significantly decrease drier management time and can increase daily output. The automation options available are tractor driven automatic empty, electric driven automatic empty, standard automatic and advanced automatic.



TRACTOR  
DRIVEN AUTO-  
MATIC  
EMPTY



ELECTRIC  
DRIVEN  
AUTOMATIC  
EMPTY



STANDARD AU-  
TOMATIC



ADVANCED  
AUTOMATIC

## FUEL

Fuelling the burner of a grain drier is the largest single operating expense and generally accounts for over half the total operating cost. These figures may vary depending on fuel selection. Fuel options include diesel, kerosene or LPG.



DIESEL



KEROSENE



LPG



METHANE  
& BIOGAS



FSN 15 T - Tractor drive, oil fired

# OPTIONS

## FILLING

There is a wide range of filling options for Mecmar grain driers. Options include standard loading hopper, shortened loading hopper, stubby loading hopper and pit loading auger.



STANDARD HOPPER



SHORTENED HOPPER



STUBBY HOPPER



PIT AUGER

## EMPTYING

Mecmar grain driers have a choice of emptying options. The grain can be emptied either through the screen to both sides, over the screen to either side, over the screen to both sides or through an electric cross auger. All emptying systems may be customised to suit individual requirement.



THROUGH SCREEN BOTH SIDES



OVER SCREEN EITHER SIDE



OVER SCREEN BOTH SIDES



ELECTRIC CROSS AUGER

## CROP CLEANING

The crop sample can be improved during drying using the screen cleaner and an aspirator if fitted. To control dust around the grain drier a bubble top auger and solid screens on the bottom cone help to create a cleaner environment.



SCREEN CLEANER



ASPIRATOR



BUBBLE TOP CENTRAL AUGER



SOLID SCREENS



Mecmar grain driers prepared for delivery



Central auger gearbox



On-board three phase generator



Through screen gravity empty to both sides



Stainless steel screens and galvanized structure



Galvanized structure



FSN 12 F - Four motor electric drive, oil fired, aspirator